

IPOB-SB4IR: Specifications


4mp IP Network Bullet Camera Weatherproof with IR



Key Features:

- 4 Mega Pixel (2560 x 1440) Max: 2560 x 1440
- H.265 Video coding
- ICR auto switch, true day / night
- 65 ~ 95 feet IR night view distance
- 3D DNR, WDR
- ROI coding
- Supports local CVBS video output and one-way audio
- Supports PoE power supply
- Supports smart phone, iPad, remote monitoring
- Supports three streams

Dimensions:



Compatible Camera Mounts:

Part Number: JB-SB-BR



Model#: IPOB-SB4IR	
Camera	
Image Sensor	1 / 3 "CMOS
Image Size	2560 x 1440
Electronic Shutter	1 / 25 s ~ 1 / 100000 s
Min. Illumination	0.05 lux @F1.2,AGC ON; 0 lux with IR
Lens	3.6mm
Lens Mount	M12
Angle Adjustment	Any Angle
Image	
Video Compression	H.265/ H.264 / MJPEG
Resolution	4MP (2560×1440), 3MP (2304×1296), 720P (1280×720), D1, CIF, 480×240 1080P (1920×1080),
Main stream	60Hz : (1 ~ 30fps) / 1080P(1 ~ 30fps) / 720P(1 ~ 30fps) 50Hz : (1 ~ 25fps) / 3MP(1 ~ 25fps) / 1080P(1 ~ 25fps) / 720P(1 ~ 25fps)
Bit rate	64 Kbps ~ 8 Mbps
Encode Mode	VBR / CBR
Quality	Five levels under VBR; Freely adjustable under CBR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. Adjustable through client software or web browser
Interfaces	
Network	RJ45
Audio	One-way audio (MIC IN × 1)
Video Output	CVBS video output (BNC × 1)
Functions	
Remote Monitoring	IE browsing, CMS remote control
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Protocol	TCP / IP, UDP, DHCP, NTP, R Protocol TSP, PPPoE, DDNS, SMTP, FTP
Storage	Network remote storage
Smart Alarm	Motion Alarm
Day & Night	ICR
PoE	Yes
IR Distance	65-95ft (20~30m)
Water-proof	IP66
Other	
Power Supply	DC 12V / PoE
Power Consumption	< 2.5W
IR Consumption ON	< 6W
Operating Environment	- 20 °C ~ 50 °C, 10 % ~ 90 % humidity
Dimensions (mm)	ø 87 × 219
Weight (net)	608g
Installation	Wall mounting, pendent mounting