

IPOB-SB4IRZA: Specifications


4mp IP Bullet Camera Weatherproof with IR & Motorized Zoom



Key Features:

- 4 Mega Pixel (2560 x 1440)
- H.265 video encoding
- 3.3~12mm Motorized Zoom
- ICR auto switch, true day / night
- 98 ~ 160 feet IR night view distance
- 3D DNR, digital WDR
- ROI coding
- Supports local CVBS video output and Two-way audio
- Supports PoE power supply
- Supports smart phone, iPad, remote monitoring
- Supports three streams

Dimensions:



Compatible Camera Mounts:



Part#: JB-SB-BR



Part#: JB-SB-UNIR

Model#: IPOB-SB4IRZA	
Camera	
Image Sensor	1/3" CMOS
Image Size	2688 x 1520
Electronic Shutter	1 / 25 s ~ 1 / 100000 s
Min. Illumination	0.05 lux @F1.2,AGC ON; 0 lux with IR
Lens	3.3~12mm
Angle Adjustment	Any Angle
Image	
Video Compression	H.265/ H.264 / MJPEG
Resolution	4MP (2560x1440), 3MP (2304x1296),1080P (1920x1080), 720P (1280x720), D1, CIF, 480x240
Main stream	60Hz : (1 ~ 30fps) / 1080P(1 ~ 30fps) / 720P(1 ~ 30fps) 4MP 4MP 3MP(1 ~ 30fps) / 50Hz : (1 ~ 25fps) / 3MP(1 ~ 25fps) / 1080P(1 ~ 25fps) / 720P(1 ~ 25fps)
Bit rate	64 Kbps ~ 10 Mbps
Encode Mode	VBR / CBR
Quality	Five levels under VBR; Freely adjustable under CBR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. Adjustable through client software or web browser
Interfaces	
Network	RJ45
Audio	Two-way audio (MIC IN x 1, MIC OUT x 1)
Video Output	CVBS video output (BNC x 1)
Storage Card	Support TF card, up to 128GB
RS485	Yes
Alarm	Input: 1ch Output: 1ch
Functions	
Remote Monitoring	IE browsing, CMS remote control
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Protocol	TCP / IP, UDP, DHCP, NTP, R Protocol TSP, PPPoE, DDNS, SMTP, FTP
Storage	TF card local storage, Network remote storage
Smart Alarm	Motion Alarm, sensor alarm
Day & Night	ICR
PoE	Yes
IR Distance	98-160ft (30 ~ 50m)
Water-proof	IP66
Other	
Power Supply	DC 12V / PoE
Power Consumption	< 2.5W
IR Consumption ON	< 6.5W
Operating Environment	- 20 °C ~ 50 °C, 10 % ~ 90 % humidity
Dimensions (mm)	ø 109 x 284
Weight (net)	1115g

Specification Subject to change without Notice*